

INTERCEPTOR™ Product Line



The INTERCEPTOR™ line of products are the industry's most advanced devices for use in Alarmed Protected Distribution Systems (PDS).

INTERCEPTOR Models



INTERCEPTOR™ monitors two or more dark (spare, unused) fibers within the cables carrying the classified information. INTERCEPTOR supports standard single-mode or multimode fiber optic cables and can be used to secure existing fiber optic cables. Using patented hub and spoke technology, a single INTERCEPTOR utilizing one rack space can monitor up to eight continuous optical circuits (zones), providing protection for multiple remote buildings or many dozens of user drops per zone in a facility.

OPTIONS:

INTERCEPTOR+Plus™ monitors active (live, data transmitting) fibers in cases where no dark data fibers are available. Please call or visit our website for details.

INTERCEPTOR™ Aerial optimized for aerial outside plant deployments.



INTERCEPTOR™ CS is a bundled solution consisting of the INTERCEPTOR and CyberSecure Infrastructure Management System, a software application that works with NIS monitoring products to provide an end-to-end solution including the ability to centrally manage alarms and create standard operating procedures. INTERCEPTOR CS also differs from INTERCEPTOR with specialized firmware and hardware components such as 100BASE-T Ethernet connections and a unidirectional simplex optical communications port for sporting alarms to an external device.

OPTIONS:

The **Cross-Domain Communications Unit** receives alarms from the unidirectional simplex optical communications port on the INTERCEPTOR CS and reports those alarms to a NIPR network.

The **StopLight™ Optical Interface** is a remotely configurable fiber optic panel that interfaces with the INTERCEPTOR CS to shut off data in alarmed zones and limit access to classified information during an intrusion attempt while continuing to monitor the Alarmed PDS network.

INTERCEPTOR™ and INTERCEPTOR™ CS are available with front or rear optical connection capability. Multimode INTERCEPTORs support desensitized lead in cables.

INTERCEPTOR™ Product Line



CyberSecure IMS Software



CyberSecure Infrastructure Management System™ (IMS) is a software application that works with NIS optical monitoring products to enable centrally managed, live monitoring of critical network infrastructure from anywhere in the world. CyberSecure IMS simplifies information assurance (IA) management, creates site specific CNSSI 7003 (formally NSTISSI 7003) compliant standard operating procedures, and generates a unique case resolution audit trail, providing robust protection against physical infrastructure intrusion attempts. A unique benefit of the IMS solution called Fiber Forensics™, provides investigators with critical information to assist in profiling methods of attack, helping to prevent future attacks.

Manhole Protection System™



The **Manhole Protection System™ (MPS)** continuously monitors the position of manhole and handhole covers and immediately reports a change at any cover. Thousands of covers may be monitored simultaneously if desired, and every cover is individually identified and mapped. Individual identification allows exact location of any attempt to access underground communication systems through a manhole and/or handhole on which a sensor has been installed, and facilitates an immediate focused response by security or law enforcement personnel via the CyberSecure IMS™ Infrastructure Management software application. MPS™ sensors contain no electronic components, require no electrical power, and emit no signals. Because no electricity is involved at any MPS™ sensor location, the sensors are intrinsically safe under all conditions.

OPTIONS:

The **Manhole Protection System™ (MPS) Sensors** utilize a single strand of standard single-mode fiber (SMF) and are inherently immune to electromagnetic and radio frequency interference, emit no signals, and cannot be bypassed without detection. MPS sensors are environmentally rugged, with an IP66 industrial standard package configuration, and may be integrated into virtually any manhole and/or handhole. MPS sensors are designed for the varying environmental conditions often found in manholes and handholes.

The **Manhole Protection System™ (MPS) Controller** connects the sensors using SMF-28 fiber to/from each group of MPS™ sensors (up to 16 channels, each comprised of up to 35 sensors). The MPS™ controllers come in 8-Channel (250+ sensors) and 16-Channel (500+ sensors) models.

